

## WRAP AROUND WAC Heat Shrink Wrap Around Sleeve



Crosslinked polyolefin wrap around open sleeve provided with slide-on metal channels and manufactured with an inner layer of hot-melt adhesive. Used in cable repair and splicing applications.

Tipo standard Standard size	Rif. Ordine Ordering info	Lunghezza /Lenght	Espanso/Expanded	Termoristretto/Recovered	
		L (mm)	D (mm)	D (mm)	S min. (mm)
WAC 50/15	FN2636	1000	50	15	1,5
	FN8886	1500			
WAC 75/22	FN5954	1000	75	22	1,5
	FN5926	1500			
WAC 105/30	FN5955	1000	105	30	1,5
	FN7609	1500			
WAC 146/38	FN5956	1000	146	38	1,5
	FN7393	1500			
WAC 188/55	FN5957	1000	188	55	1,5
	FN9972	1500			

Proprietà/Property	Unità di misura/Units	Valore/Value	Norma/Standard
Resistenza a trazione/Tensile strength	N/mm <sup>2</sup>	≥20	ASTM D 638
Allungamento a rottura/Elongation at break	%	≥400	ASTM D 638
Assorbimento d'acqua/Water absorption	%	≤0,2	ISO 62
Rigidità dielettrica/Dielectric strength	kV/mm	≥12	ASTM D 149
Temperatura di esercizio/Continuous temperature range	°C	-50 ÷ +100	IEC 60587 84
Colore standard/Standard colour	Nero/Black		